



PBL8MDF Pro Series

Features

Resolution	: 8MP
Effective Pixels	: 3864(H)*2192(V)
Lens Type	: Fixed focal lens, 2.8, 3.6, and 6 mm optional
Infrared LED	: 42μ x 4PCS
Infrared Distance	: 40M
ONVIF	: Support ONVIF 19.12(Profile S/T/G)
P2P	: YES
POE	: Internal, Support IEEE 802.3af
Smart Phone	: iPhone, Android
Day/Night	: Color/ B&W (IR-CUT)
Audio	: Optional Audio IN/OUT
Alarm	: Optional 1 Channel Input/Ouput
SD Card Slot	: Optional Internal, Support Max 1TB, Built in 4G Storage

Specifications

Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Resolution	8MP
Effective Pixels	3864(H)*2192(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
Audio Compression	G711A/U,AAC
TV System	PAL/NTSC
Electronic Shutter Time	Auto: 1/3-1/100000Sec
Minimum Illumination	Color: 0.01 lux@F1.6, AGC ON; B/W : 0 lux with IR
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Lens	
Focal Length & FOV	2.8 mm, horizontal FOV 96°, vertical FOV 52°, diagonal FOV 114° 3.6 mm, horizontal FOV 84°, vertical FOV 48°, diagonal FOV 97° 6 mm, horizontal FOV 53°, vertical FOV 30°, diagonal FOV 60°
Lens Type	Fixed focal lens, 2.8, 3.6, and 6 mm optional
Focus Control	Fixed
Aperture	F1.6
Pixels	8MP
Night Vision	
Infrared LED	42μ x 4PCS
Infrared Distance	40M
IR Status	Auto Control
IR Power On	Smart, Manual & Timed mode
Network	
Ethernet	RJ-45 (10/100Base-T)
Wireless	N/A
Protocol	TCP/IP,IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP, SNMP,Qos,802.1x
ONVIF	Support ONVIF 19.12(Profile S/T/G)
P2P	YES
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	3840*2160@25fps 3072*2048@25fps
Main Stream 2	2592*1536@25fps 2560*1440@25fps
Main Stream 3	1920*1080@25fps 1280*720@25fps
Sub Stream 1	1280*720@25fps 720*480@25fps
Sub Stream 2	352*288@25fps
Sub Stream 3	N/A

Tri Stream	1280*720@25fps 720*480@25fps 352*288@25fps
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, Android
AI Function	
Intelligent Analysis	Face Detection,Intrusion Detetion, Line Cross Detetion, Loiter Detetion, People Gather Detecion(based on human detection),Motion detection based on human detection,Vehicle Detection
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast / Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering, HLC, Distortion
Full Color	N/A
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	140dB
Motion Detection	Support(support enable the detection based on human movement only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Czech, Vietnamese
Interface	
Audio	Optional Audio IN/OUT
Alarm	Optional 1 Channel Input/Opuput
SD Card Slot	Optional External, Support Max 1TB,Built in 4G Storage
RS485	N/A
General	
Housing	Metal ,IP67
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 950mA
Dimension	∅ 140 x 128(H)mm
Weight	1200g

Malaysia solution provider



Unit 17-03 &17-04, Tower 1, Faber Towers, Jalan Desa Bahagia, Taman Desa, 58100 Kuala Lumpur Direct Phone: +60379846781 ; Mobile: +60122352710
www.prismabytes.com Email: bd@prismabytes.com