

PoE Industrial Ethernet Optical Switch

PoE 10/100Mbps TP 4-Ports + 100Mbps-FX SFP 2-Slots



- 802.3af PoE 15.4 Watt (Max. 60W)
- DIN-Rail installable
- Power polarity protection circuit built-in
- DC 48V (terminal block) power supply method
- IEEE802.3af Power Over Ethernet / PSE
- 4-Ports (PoE 802.3af) + SFP 2-Slots industrial optical switch
- 100Mbps PoE switch suitable for industrial environment

SFC300-PoE

Ordering Information

| | | |
|-----------------------|----------------|--|
| Technology | Standard | IEEE 802.3 10Base-T Ethernet IEEE 802.3U 100Base-TX/100Base-FX IEEE 802.3af Power Over Ethernet Standards |
| Interface | RJ45 Port | POE 10/100Mbps TP 4-Ports, Auto MDI/MDI-X UTP/STP Cat. 3, 4, 5, 6 Cable EIA/TIA-568 100-ohm (Transmission Distance 100m) Provides DC 48V Power Over RJ-45 Ethernet Cable to Devices with Ethernet Port |
| | Fiber Port | 100Mbps-FX, SFP 2-Slots Multi-mode : 62.5/125 μ m(2km) Single-mode : 9/125 μ m(~ 100km) |
| | LED Indication | Per unit : Power, Fault TX Port (Link/Act, FDX/HDX, Speed), FX Port (Link/Act, FDX/HDX, Speed) |
| Performance | Throughput | 100Mbps |
| | Mac Address | 2K MAC Address table |
| | PoE | 15.4Watt (MAX 60W) per port |
| | Installation | DIN-Rail, Panel mounting |
| Operating Environment | Temperature | Operating: - 40°C ~ 80°C, Storage: - 45°C ~ 85°C |
| | Humidity | 5 ~ 95% (Non-condensing) |
| Power Supply | | DC 48V |
| Dimension | | 55mm(W) x 120mm(D) x 150mm(H) |

Ordering Information

| Model Type | Specification |
|------------|--|
| SFC300-POE | POE 10/100Mbps TP 4-Ports + 100Mbps-FX SFP 2-Slots |
| SFP-SM | SFP(155Mbps) module, Single-mode, Transmission Distance 20km, 1310nm, LC Connector |
| SFP-MM | SFP(155Mbps) module, Single-mode, Transmission Distance 20km, 1310nm, LC Connector |
| AD1240-48S | Industrial power supply, 240W, 52V |