

PoE 10/100/1000Mbps 10-Ports Optical Switch

PoE 10/100/1000Mbps TP 8-Ports + SFP 2-Slots



- PoE 8-Ports + 100/1000Mbps 2-Slots SFP module
- IEEE 802.3at PoE 30.8W 8-Ports (Max 120W)
- Web based management, SNMP
- Auto MDI/MDI-X
- IGMP Snooping v1, v2, v3
- Auto Scan Manager Program

Specifications

Technology	Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.1Q VLAN Tagging IEEE 802.1p Class of Service IEEE 802.3ab 1000Base-T IEEE 802.3x Flow Control and Back Pressure IEEE 802.3af Power over Ethernet	IEEE 802.3ad Port trunk with LACP IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3at Power over Ethernet IEEE 802.1w Rapid spanning tree IEEE 802.1d Spanning Tree
Interface	RJ45 Port	POE 10/100/1000Mbps TP 8-Ports, Auto-Negotiation, Auto MDI-X	
	Fiber Port	SFP 2-Slots 1000Mbps-SX/LX SFP, 100Mbps-FX SFP, Speed auto detection	
	LED Indication	System : Power Ports : 10/100/1000Mbps Link/Act, POE In-Use, SFP Link	
Performance	Back Plane	Switch Fabric 20Gbps, 8K MAC Address table, Jumbo Frame 9.6Kbytes	
	PoE	PoE Power Budget: Max. 120Watt Number of PD@7Watt / 8Port Number of PD@15.4Watt / 7Port Number of PD@30.8Watt / 4Port	
Operating Environment	Temperature	Operating: 0°C ~ 60°C, Storage: -20°C ~ 80°C	
	Humidity	5 ~ 95% (Non-condensing)	
Power Supply		100~240VAC, 50/60Hz	
Dimension		330.5mm(W) x 153mm(D) x 44mm(H)	

Ordering Information

Model Type	Specification
SFC400HP	POE 10/100/1000Mbps TP 8-Ports + SFP 2-Slots, Management Gigabit PoE Optical Switch
SFP-SX	SFP(1.25Gbps) module, Multi-mode, Transmission Distance 220/550m, 850nm, LC Connector
SFP-LX	SFP(1.25Gbps) module, Single-mode, Transmission Distance 20km, 1310nm, LC Connector
SFP-MM	SFP(155Mbps) module, Multi-mode, Transmission Distance 2km, 1310nm, LC Connector
SFP-SM	SFP(155Mbps) module, Single-mode, Transmission Distance 20km, 1310nm, LC Connector