

100Mbps-TX & FX 8-Port Ethernet Fiber Optic Switch

100Mbps TP 2-Ports + Fiber 6-Port Fiber Optic Switch



- IEEE802.3 10Base-T, IEEE802.3u 100Base-TX
- Fiber Optic 100Mbps-FX, Ethernet 10/100Mbps-TX
- Switch Operation/Connection status LED display
- Auto MDI-X TP port, Auto Negotiation
- Built-in power supply (110~220VAC, DC48V option)
- 19"RACK installation
- Operating temperature : 0°C~60°C
-

Specification

| | | |
|--------------------|------------------|---|
| Technology | - Standard | IEEE 802.3 10Base-T IEEE 802.3u 10/100Mbps-TX / 100Mbps-FX |
| Interface | - RJ45 Ports | 10/ 100Mbps TP, Auto Negotiation, Auto MDI / MDI-X TP/STP Cat. 3,4,5 Cable, EIA/TIA-568 100-ohm (100m) |
| | - Fiber Ports | 100Mbps-FX (SC Connector Type) Single mode : 9/125 μ m (~100km) |
| | - LED Indicators | Power, FD, Link/Act, Speed |
| Performance | - Throughput | 100Mbps |
| Environment | - Temperature | Operation: 0°C ~ 60°C, Storage: -20°C ~ 80°C |
| | - Humidity | 5 ~ 95% (Non-condensing) |
| | - Installation | 19" Rack Installation |
| Input Power | | 110~220VAC, 50/60Hz |
| Dimension | | 317mm(W) x 150mm(D) x 35mm(H) |

Ordering Information

※ For Single mode long distance and WDM type, please inquire to the manufacturer

| Model Type | Specification | Model Type | Specification |
|-------------|--|-------------|--|
| SFC400-SCM | Fiber1+TP7, Multi mode, 2km,1310nm, SC Connector | SFC400-SCS | Fiber1+TP7, Single mode, 20km,1310nm, SC Connector |
| SFC400-SCM2 | Fiber2+TP6, Multi mode, 2km,1310nm, SC Connector | SFC400-SCS2 | Fiber2+TP6, Single mode, 20km,1310nm, SC Connector |
| SFC400-SCM4 | Fiber4+TP4, Multi mode, 2km,1310nm, SC Connector | SFC400-SCS4 | Fiber4+TP4, Single mode, 20km,1310nm, SC Connector |
| SFC400-SCM6 | Fiber6+TP2, Multi mode, 2km,1310nm, SC Connector | SFC400-SCS6 | Fiber6+TP2, Single mode, 20km,1310nm, SC Connector |
| | | SFC400-SCS8 | Fiber8, Single mode, 20km,1310nm, SC Connector |